

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 21.02.2016

Revision: 21.02.2016

Version number 2

---

### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### 1.1 Product identifier

**Trade name:** arecal High-strength pipe thread sealant 50g

**Article number:** 0893 300 002

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

**Application of the substance / the mixture** Adhesives

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

RECA-uk ltd

Doranda Way, West Bromwich

GB-West Midlands B71 4LU

Telefon: +44 121 5250525

**Further information obtainable from:** info@recanorm.de

**Department issuing MSDS:** info@recanorm.de

**1.4 Emergency telephone number:** 111

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) No 1272/2008**

The product is not classified according to the CLP regulation.

---

#### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008** Void

**Hazard pictograms** Void

**Signal word** Void

**Hazard statements** Void

#### 2.3 Other hazards

**Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

---

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

**Description:** Adhesive

**Dangerous components:** Void

---

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

**General information:** Remove any clothing soiled by the product.

##### After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:** After contact with skin, wash with plenty of soap and water.

##### After eye contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

(Contd. on page 2)

---

**Trade name:** arecal High-strength pipe thread sealant 50g

---

(Contd. of page 1)

**After swallowing:**

Rinse out mouth and then drink plenty of water.

If swallowed, do not induce vomiting: seek medical advice and show this container or label.

**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

---

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.**5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Nitrogen oxides (NO<sub>x</sub>)

Carbon monoxide and carbon dioxide

Danger of forming toxic pyrolysis products.

Under certain fire conditions, traces of other toxic gases cannot be excluded.

**5.3 Advice for firefighters****Protective equipment:**

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

**Additional information**

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

---

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Avoid contact with the eyes and skin.

**6.2 Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

**6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

**6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 10 for information on "stability and reactivity".

See Section 13 for disposal information.

---

**SECTION 7: Handling and storage****7.1 Precautions for safe handling** No special precautions are necessary if used correctly.**Information about fire - and explosion protection:**

No special precautions are necessary if used and stored according to specifications.

**7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.**Information about storage in one common storage facility:** Not required.**Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

**7.3 Specific end use(s)** No further relevant information available.

(Contd. on page 3)

---

**Trade name:** arecal High-strength pipe thread sealant 50g

---

(Contd. of page 2)

**SECTION 8: Exposure controls/personal protection****Additional information about design of technical facilities:** No further data; see item 7.**8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

**Additional information:** The lists valid during the making were used as basis.**8.2 Exposure controls****Personal protective equipment:****General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

**Protection of hands:**

Protective gloves on prolonged contact with skin.

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves**

Find below a list of appropriate protective gloves for chemical surrounding:

Permeation time / penetration time: = 480 minutes (DIN EN 374):

Naturlatex I , Nr. 0395 oder 0403

Chloropren Nitril I, Nr. 0727

Nitril I, Nr. 0730, 0732, 0733, 0736, 0737, 0738, 0739 oder 0836

Viton, Nr. 0890

Butyl II, Nr. 0897

Butyl, Nr. 0898

Permeation time / penetration time: = 240 minutes (DIN EN 374):

Chloropren Nitril II, Nr. 0717

Nitril VI, Nr. 0754

Nitril V, Nr. 0764

of KCL company (e-mail: [vertrieb@kcl.de](mailto:vertrieb@kcl.de)).

The recommendation is based exclusively on the chemical compatibility and the test according to EN374 under laboratory conditions.

Requirements can vary according to the use. Therefore, please always take into account the glove supplier's recommendations.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:** Avoid contact with the eyes.

---

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****General Information****Appearance:**

**Form:** Fluid

**Colour:** Red

**Odour:** Mild

**Odour threshold:** Not determined.

(Contd. on page 4)

---

**Trade name:** arecal High-strength pipe thread sealant 50g

---

(Contd. of page 3)

<b>pH-value:</b>	Not determined.
<b>Change in condition</b>	
<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	Undetermined.
<b>Flash point:</b>	> 100 °C
<b>Flammability (solid, gaseous):</b>	Not applicable.
<b>Ignition temperature:</b>	
<b>Decomposition temperature:</b>	Not determined.
<b>Self-igniting:</b>	Product is not self-igniting.
<b>Danger of explosion:</b>	Product does not present an explosion hazard.
<b>Explosion limits:</b>	
<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.
<b>Vapour pressure:</b>	Not determined.
<b>Density at 25 °C:</b>	1,1 g/cm <sup>3</sup>
<b>Relative density</b>	Not determined.
<b>Vapour density</b>	Not determined.
<b>Evaporation rate</b>	Not determined.
<b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
<b>Partition coefficient (n-octanol/water):</b>	Not determined.
<b>Viscosity:</b>	
<b>Dynamic at 25 °C:</b>	6 000 - 7 000 mPas (Brookfield (5/20))
<b>Kinematic:</b>	Not determined.
<b>9.2 Other information</b>	No further relevant information available.

---

## SECTION 10: Stability and reactivity

**10.1 Reactivity** No further relevant information available.

### 10.2 Chemical stability

#### **Thermal decomposition / conditions to be avoided:**

No decomposition if used and stored according to specifications.

Protect from heat and direct sunlight.

**10.3 Possibility of hazardous reactions** Reacts with metal-salts.

**10.4 Conditions to avoid** No further relevant information available.

**10.5 Incompatible materials:** No further relevant information available.

#### **10.6 Hazardous decomposition products:**

No dangerous products of decomposition if used and stored according to specifications.

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

**Acute toxicity** Based on available data, the classification criteria are not met.

#### **Primary irritant effect:**

**Skin corrosion/irritation** Repeated exposure may cause skin dryness or cracking.

**Serious eye damage/irritation** Slight irritant effect possible.

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

#### **Additional toxicological information:**

No experimentally found toxicological data are available for this preparation.

#### **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

(Contd. on page 5)

**Trade name:** arecal High-strength pipe thread sealant 50g

(Contd. of page 4)

**Reproductive toxicity** Based on available data, the classification criteria are not met.  
**STOT-single exposure** Based on available data, the classification criteria are not met.  
**STOT-repeated exposure** Based on available data, the classification criteria are not met.  
**Aspiration hazard** Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

### 12.1 Toxicity

**Aquatic toxicity:** No further relevant information available.

**12.2 Persistence and degradability** No further relevant information available.

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

### Additional ecological information:

#### General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Danger to drinking water if even small quantities leak into the ground.

Do not allow product to reach ground water, water course or undiluted sewage system.

### 12.5 Results of PBT and vPvB assessment

**PBT:** Not applicable.

**vPvB:** Not applicable.

**12.6 Other adverse effects** No further relevant information available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

**Recommendation** Disposal must be made according to official regulations.

#### European waste catalogue

08 00 00 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 04 00 wastes from MFSU of adhesives and sealants (including waterproofing products)

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

#### Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.

## SECTION 14: Transport information

### 14.1 UN-Number

ADR, IMDG, IATA Void

### 14.2 UN proper shipping name

ADR, IMDG, IATA Void

### 14.3 Transport hazard class(es)

ADR, ADN, IMDG, IATA

Class Void

### 14.4 Packing group

ADR, IMDG, IATA Void

**14.5 Environmental hazards:** Not applicable.

**14.6 Special precautions for user** Not applicable.

### 14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

UN "Model Regulation": Void

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### National regulations:

**Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

(Contd. on page 6)

# Safety data sheet

according to 1907/2006/EC, Article 31

Page 6/6

Printing date 21.02.2016

Revision: 21.02.2016

Version number 2

---

**Trade name:** arecal High-strength pipe thread sealant 50g

---

(Contd. of page 5)

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

---

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

---

— GBGEN —